

Gefen DVI KVM Extender EXT-CAT5-1000HD



Extends one DVI and USB up to 200 feet (60 meters) away

The Professional Series CAT5•1500HD extends your DVI display and USB up to 200 feet away from your DVI or HDMI™ source. The CAT5•1500HD is now available with a built in 4 port USB hub on the receiver unit.

How it works

The CAT5•1500HD sender unit sits next to your computer. The cables supplied with the CAT5•1500HD connects your DVI source and USB to the send unit. The CAT5•1500HD receiver unit sits next to your DVI display - up to 200 feet away. The display and USB plug into the back of the CAT5•1500HD receiver unit. Two CAT-5 cables connect the CAT5•1500HD-S and the CAT5•1500HD-R units to each other.

Note: The CAT5•1500HD is HDCP compliant.

DVI, HDCP & HDMI Defined

Package Includes:

- * CAT5•1500HD-S
- * CAT5•1500HD-R
- * One 6 foot DVI to DVI Cable
- * One 6 foot USB Cable
- * Two 5V Power Supply
- * Rack ears
- * User's Manual

Features:

- * Extends any DVI compliant device up to 150 feet (45 meters) from the computer at 1920x1200
- * Extends any DVI compliant device up to 200 feet (60 meters) from the computer at 1280x1024
- * Extends USB 1.1 compliant devices up to 200 feet
- * Uses CAT-5e cable for DDC and control signals
- * Video is transmitted digitally for zero signal loss over CAT5-e cable
- * Supports resolutions up to 1080p, 2K, and 1920 x 1200
- * Supports DDWG standard for DVI compliant monitors
- * Includes rack ears
- * HDCP compliant

Specifications:

- * Video Amplifier Bandwidth: 165 MHz
- * Single Link Range: 1080P/1920 x 1200
- * Input Video Signal: 1.2 volts p-p
- * Input DDC Signal: 5 volts p-p (TTL)
- * DVI Connector: DVI-I (29 pin) female (digital only)
- * USB Input: USB type "B" connector
- * USB Output: four USB type "A" connectors
- * Link Connector: RJ-45 Shielded
- * Power Supply: 5V DC
- * Power Consumption: 20 watts (max)
- * Dimensions: 17" W x 1.75"H x 4.375" D
- * Shipping Weight: 10 lbs.